

# MODEL 130 V4

## SPECIFICATIONS



Model	a. E130DPL b. E130DSL c. E130DPX d. E130DCX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c. 635 (25") White d. 635 (25") White
Weight kg (lbs)	a. / b. 177 (390) c. / d. 184 (405)
Engine Type	Loop Charged V4 60° E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	1726 (105.4)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	97 kw (130 HP) @ 5750 RPM
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	a. / b. 2.0:1 c. / d. 2.25:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.

\*\* 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.