

MODEL 300 V6

SPECIFICATIONS



Model	a. E300DSL b. E300DPX c. E300DCX d. E300DPZ e. E300DCZ
Shaft Length mm (in) / Color	a. 508 (20") White b. / c. 635 (25") White d. / e. 762 (30") White
Weight kg (lbs)	a. 233 (514) b. / c. 240 (528) d. / e. 242 (534)
Engine Type	Loop Charged V6 90° E-TEC Direct Injection
Bore x Stroke mm (in)	98 x 76 (3.854 x 3.000)
Displacement cc (cu in)	3441 (210)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	224 kw (300 HP) @ 5500 RPM
Full Throttle Operating Range	5000-6000 RPM
Gear Ratio	1.85:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 2 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.